

60 TON LATTICE BOOM OFFSHORE CRANE FOR SALE - AVAILABLE IMMEDIATELY - CRANE NEVER USED



- 60 ton capacity lattice boom offshore crane
- Type: wireluffing diesel hydraulic
- Available immediately
- Design Rules: API-2C offshore
- Classification Society: DNV
- Hazardous Area Classification: Zone 2 IIA-T3
- Fem Classification: – Appliance group: A4-Q2-U4
 - Machinery group: M4-L2-T4
- Power supply 1: 480V-60Hz-3Ph
- Power consumption 1: 14,5 kW
- Power supply 2: 240V-60Hz-1Ph
- Power consumption: 1,2 kW
- Total weight: 168 ton

Capacities Main Hoist

- Max. lift capacity 3 falls: 60 ton
- Max. lift capacity 2 falls: 40 ton
- Max. outreach: 45,7 metres
- Min. outreach: 9,0 metres
- Wave height max.: 2,5 metres
- Load / outreach: see load chart here below
- Hook travel: 70 metres
- Hoist speed (3 falls / 60 ton): 0-22 m/min
- Hoist speed (2 falls / 40 ton): 0-33 m/min

Capacities Aux. Hoist

- SWL max.: 7,5 ton
- Manriding: 1,0 ton
- No. of falls: 1
- Outreach max.: 46,7 metres
- Outreach min.: 10,0 metres
- Wave height max.: 2,5 metres
- Load / outreach: see load chart here below
- Hook travel: 70 metres
- Hoist speed: 0-60 m/min

Slewing (360 degrees)

- Slewing speed: 0-1 rpm

Price: on request

Delivery: ex-location Europe

Downloads

– [60 tons OffshoreCrane_loadchart](#)

Images links

https://www.offshore-crane.com/wp-content/uploads/2014/04/AVAILABLE-AT-OFFSHORE-CRANE.COM_60-TON-LATTICE-BOOM-OFFSHORE-CRANE_1.jpg

https://www.offshore-crane.com/wp-content/uploads/2014/04/AVAILABLE-AT-OFFSHORE-CRANE.COM_60-TON-LATTICE-BOOM-OFFSHORE-CRANE.jpg

Equipment details believed correct but not guaranteed.

All equipment is offered subject to prior sales.

Basic terms of sale is that the equipment is to be sold as seen, no warranty provision.
Transfer of Ownership on receipt of full payment.

Please advise if interested and we will organise an on-site inspection of the equipment offered.